

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 353 252 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
15.10.2003 Bulletin 2003/42

(51) Int Cl.7: **G05B 23/02**(21) Application number: **03075855.1**(22) Date of filing: **24.03.2003**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT RO SE SI SK TR**
Designated Extension States:
AL LT LV MK

- Ikegami, Roy
Seattle, WA 98118 (US)
- Haugse, Eric D.
Normandy Park, WA 98166 (US)

(30) Priority: **04.04.2002 US 116653**

(71) Applicant: **THE BOEING COMPANY**
Seattle, Washington 98124-2207 (US)


(74) Representative:
Land, Addick Adrianus Gosling et al
Arnold & Siedsma
Sweelinckplein 1
2517 GK Den Haag (NL)

(72) Inventors:
• Trego, Angela
Richland, WA 99352 (US)

(54) Vehicle condition monitoring system

(57) The present invention is a system and method for monitoring conditions of a vehicle and generating a maintenance plan according to the monitored conditions. The system includes one or more sensors 22 and a data acquisition unit 26 located within the vehicle 21. The one or more sensors 22 generate signals of a condition from various locations within the vehicle 21. The data acquisition unit 26 stores the generated sensor sig-

nals at a first sampling rate. The system also includes a structural condition management system 30 that receives the stored sensor signals from the data acquisition unit. The structural condition management system 30 is external to the vehicle 21. The structural condition management system 30 processes the transmitted sensor signals based on one or more associated predefined condition assessment algorithms and generates a maintenance plan based on the processed sensor signals.

*Fig. 1.*

Description

FIELD OF THE INVENTION

[0001] This invention relates generally to vehicle maintenance systems and, more specifically, to data acquisition relating to vehicle condition.

BACKGROUND OF THE INVENTION

[0002] Total life cycle costs for vehicles includes costs for operating and maintaining the vehicles. In many instances, vehicles must be inspected before maintenance can be performed on the vehicles.

[0003] A significant portion of the cost of inspecting vehicles, such as aircraft, for corrosion, stress or other damage is associated with obtaining access to hidden parts of the vehicle's structure. For example, for a 747-400 commercial transport aircraft over 36,000 labor hours are spent inspecting the aircraft for fatigue cracks and corrosion. Of these, 25,000 hours are spent inspecting for corrosion. Over 21,000 hours or 84% of these hours are spent gaining access to hard to inspect areas, and only 16% or 4000 hours are spent doing the actual inspection. In addition, added costs are associated with incidental damage that may be inflicted upon the structure while gaining access to hidden areas.

[0004] Therefore, there is a need to develop a system and process for reducing the time to complete vehicle inspections.

SUMMARY OF THE INVENTION

[0005] The invention provides a system and method for reducing structural condition maintenance costs by monitoring vehicle condition in real-time.

[0006] The present invention is a system and method for monitoring conditions of a vehicle and generating a maintenance plan according to the monitored conditions. The system includes one or more sensors and a data acquisition unit located within the vehicle. The one or more sensors generate signals of a condition from various locations within the vehicle. The data acquisition unit stores the generated sensor signals at a first sampling rate. The system also includes a structural condition management system that receives the stored sensor signals from the data acquisition unit. The structural condition management system is external to the vehicle. The structural condition management system processes the transmitted sensor signals based on one or more associated predefined condition assessment algorithms and generates a maintenance plan based on the processed sensor signals.

[0007] The data acquisition unit determines if the generated sensor signals need to be stored at a sampling rate different than the first sampling rate. The generated sensor signals are stored at a sampling rate different than the first sampling rate, if it is determined the stored

sensor signals need to be stored at a different sampling rate.

[0008] The one or more sensors suitably include at least one of a corrosion, humidity, pH, chloride ion (Cl⁻), metal ion, temperature, acceleration, stress, strain, pressure, load, or force sensor.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The preferred and alternative embodiments of the present invention are described in detail below with reference to the following drawings.

FIGURE 1 illustrates components of the present invention implemented in an aircraft;

FIGURE 2 illustrates the components of a data acquisition unit implemented within a vehicle; and

FIGURES 3 and 4 are flow diagrams illustrating example data acquisition processes performed by the components shown in FIGURES 1 and 2.

DETAILED DESCRIPTION OF THE INVENTION

[0010] The present invention provides a system and method for acquiring vehicle condition information in a non-intrusive, efficient manner for allowing damage and usage analysis. As shown in FIGURE 1, a condition data acquisition system 20 is located in a vehicle 21 and includes one or more sensors 22 electrically or optically coupled to a data acquisition unit 26. The sensors 22 generate electrical or photonic signals that reflect a condition in which the sensors 22 were designed to detect. The data acquisition unit 26 acquires the electrical or photonics signals from the sensors 22 and processes the received electrical or photonics signals for analysis by a structural condition management system 30 that is external to the vehicle. The data acquisition unit 26 may perform some diagnostic or prognostic preprocessing of the received signals based on the type of signal received and a predefined test to be performed on the received signals. It will be appreciated that the structural condition management system 30 is a system that is presently used in many vehicle continued maintenance programs, such as that used in the airline industry. The present invention provides an electrical or wireless connection between the data acquisition unit 26 and the structural condition management system 30 for allowing the delivery of the sensed electrical or photonics signals from the data acquisition unit 26 to the structural condition management system 30. It will be appreciated that the vehicle can be an aircraft, spacecraft, launch vehicle, sea-borne or undersea vessel, or ground-based vehicle.

[0011] A number of digital signal processing algorithms are available to be coded into the data acquisition unit 26 to perform functions such as filtering and data compression, Fourier transforms, power spectral density calculations on dynamic data, and diagnosis of the sensed structural component such as fatigue life and us-

age, overload conditions and environmental exposures, etc. The structure condition management system 30 is a computer system such as a laptop or personal computer that takes the sensor data and the coded processing algorithms and performs additional diagnostics assessments of the structural condition (health). The structure condition management system 30 includes prognostics algorithms that assess the current state (health) of the vehicle 21 to predict the condition at some future time given some assumed loading, usage, scenario, or environmental exposure. The prognostics algorithms can include crack growth or strain-life models, corrosion damage predictive models, or other residual strength and life predictive models. The structure condition management system 30 then stores the data in a format specified by vehicle maintenance personnel for the purpose of planning future maintenance actions.

[0012] Some of the sensors 22 are prepositioned in the vehicle in hidden locations that would require physical deconstruction of the vehicle for proper condition inspection to be completed using known inspection methods. [This refers to prior inspection methods] The sensors 22 are suitable off-the-shelf micro-electromechanical devices (MEMS), or extrinsic Fabry-Perot interferometric (EFPI), long-period grating (LPG), and fiber Bragg grating (FBG) fiber optic sensors. The sensors 22 suitably include corrosion, humidity, pH, chloride ion (Cl⁻), metal ion, temperature, acceleration, stress, strain, pressure, load, and force sensors. Fiber optic sensors are relatively tolerant or immune to the effects of high-temperature, high-electromagnetic interference (EMI), and highly corrosive environments. In one non-limiting example, the sensor is an LPG fiber optic moisture sensor that is located in areas of a vehicle where water can pool or cause problems, such as under floors of lavatories and galleys, inside insulation around doors, and in bilge areas.

[0013] FIGURE 2 illustrates that the data acquisition unit 26 includes an analog-to-digital (A/D) converter 40, a signal processor 44, and memory 46. The A/D converter 40 receives the signals from the sensors 22, converts the received signals into digital signal format, and sends the digital signals to the signal processor 44. The signal processor 44 processes the signals received from the sensors 22 to generate digital data and stores the digital data in the memory 46. After the structural condition management system 30 is connected to the data acquisition unit 26, the signal processor 44 retrieves the stored digital data from the memory 46 based on requests from the structural condition management system 30. In one non-limiting example, an RS-232 serial port interface allows a connection to various computer or data downloading serial port devices, such as personal data assistants, laptop computers, or a direct or wireless connection to the structural condition management system 30. It will be appreciated that other interface devices can be used to allow the data acquisition unit 26 to transmit data to external devices.

[0014] In one non-limiting embodiment, the data acquisition unit 26 is powered by a battery not coupled to any other components of the vehicle. The data acquisition unit 26 with a battery becomes a stand-alone system that does not rely on the functionality of any other vehicle system.

[0015] FIGURE 3 illustrates an exemplary process 55 performed by the condition data acquisition system 20 and the structural condition management system 30. First, at block 60, the data acquisition unit 26 receives signals from the sensors 22. An exemplary sampling process for the reception of signals is described in more detail below in FIGURE 4. Next, at block 62, the data acquisition unit 26 digitizes the received signals from the sensors 22. At block 63, the data acquisition unit 26 performs initial processing of the digitized signals based on diagnostic or prognostic algorithms executed by the unit 26. The type of diagnostic algorithm used is based on the type of sensor that sends the signal. At block 64, the data acquisition unit 26 stores the digitized and processed signals for later use. Then, at block 66, the stored digitized and processed signals are downloaded to the structural condition management system 30. The download of the stored digitized and processed signals is preferably performed at a scheduled maintenance period. Finally, at a block 68, the structural condition management system 30 processes and analyzes the downloaded digitized and processed signals according to associated diagnostic or prognostic application programs executed by the structural condition management system 30.

[0016] Results of the diagnostic or prognostic application programs produce a condition maintenance plan for the vehicle 21. The diagnostic application programs determine vehicle condition by analyzing the sensor signals. The prognostic application programs predict future vehicle condition by analyzing the sensor signals based on some assumed usage scenario. In one non-limiting example, the analyzed signal from a first corrosion sensor indicates a non-corrosion condition at the portion of the vehicle proximate to the first corrosion sensor. Thus, non-maintenance of the portion of the vehicle proximate to the first corrosion sensor is included in the structural condition maintenance plan. However, the analyzed signal from a second corrosion sensor indicates a corrosion condition existing at the portion of the vehicle proximate to the second corrosion sensor. With regards to the portion of the vehicle proximate to the second corrosion sensor, the structural condition maintenance plan includes required inspection and/or maintenance for the affected portion of the vehicle.

[0017] FIGURE 4 illustrates an exemplary sensor signal reception process 75. First, at block 80, the signals are received from the sensor at a first sampling rate. Next, at decision block 81, the process continues provided a sampling threshold has not been reached. For example, the threshold could be prescheduled maintenance shut down. At decision block 82, the signal proc-

essor 44 determines if the received signals indicate the need for a higher sampling rate. A non-limiting example of an indication for a need for a higher sampling rate is if the sensor is a temperature sensor and the received temperature signal differs from previously received temperature signals by more than a threshold amount. The analysis performed at decision block 82 is performed by a sampling signal analysis application program executed by the signal processor 44. If, at decision block 82 there is no indication for a need for a higher sampling rate, the process continues sampling at the first sampling rate. However, if at decision block 82, there is an indication for a need for a higher sampling rate, the sensor signals are sampled at a second sampling rate, which is higher than the first sampling rate, see block 84. It will be appreciated that additional sampling rates can be applied based on various sampling rate needs of the data acquisition unit 26.

[0018] While the preferred embodiment of the invention has been illustrated and described, as noted above, many changes can be made without departing from the spirit and scope of the invention. Accordingly, the scope of the invention is not limited by the disclosure of the preferred embodiment. Instead, the invention should be determined entirely by reference to the claims that follow.

Claims

1. A method for monitoring condition of structure of a vehicle, the method comprising:

generating signals relating to a structural condition of the vehicle at one or more condition sensors 22 positioned in the vehicle; and storing at a first sampling rate the generated sensor signals at a data acquisition unit 26 within the vehicle.

2. The method of Claim 1, further comprising preprocessing the generated signals based on at least one of a diagnostic or prognostic algorithm.

3. The method of Claim 1, further comprising transmitting the stored sensor signals from the data acquisition unit to the structural condition management system 30.

4. The method of Claim 3, further comprising:

processing the transmitted sensor signals at the structural condition management system 30 based on one or more associated predefined condition assessment algorithms; and generating a maintenance plan based on the processed sensor signals.

5. The method of Claim 1, wherein storing includes:

determining whether the stored signals are to be stored at a first sampling rate; and storing the generated sensor signals at a second sampling rate that is different than the first sampling rate when it is determined that the generated sensor signals are not to be stored at the first sampling rate.

6. The method of Claim 1, wherein the one or more sensors 22 include at least one of a corrosion, humidity, pH, chloride ion, metal ion, temperature, acceleration, stress, strain, pressure, load, or force sensor.

7. A system for monitoring condition of structure of a vehicle, the system comprising:

one or more sensors 22 for generating signals relating to a structural condition of the vehicle from a location in the vehicle; and a data acquisition unit 26 for storing the generated sensor signals at a first sampling rate.

8. The system of Claim 7, wherein the data acquisition unit 26 performs preprocessing of the generated signals based on at least one of a diagnostic or prognostic algorithm.

9. The system of Claim 7, further comprising a structural condition management system 30 for receiving the stored sensor signals from the data acquisition unit 26, wherein the structural condition management system 30 is external to the vehicle.

10. The system of Claim 9, wherein the structural condition management system 30 processes the received sensor signals based on one or more associated predefined condition assessment algorithms and generates a maintenance plan based on the processed sensor signals.

11. The system of Claim 7, wherein the data acquisition unit 30 determines whether the generated sensor signals are to be stored at the first sampling rate, and stores the generated sensor signals at a second sampling rate that is different than the first sampling rate when it is determined that the stored sensor signals are not to be stored at the first sampling rate.

12. The system of Claim 7, wherein the one or more sensors 22 include at least one of a corrosion, humidity, pH, chloride ion, metal ion, temperature, acceleration, stress, strain, pressure, load, or force sensor.

13. The system of Claim 7, wherein the system includes a self-contained power supply.
14. A vehicle comprising:
- one or more sensors 22 for generating signals relating to a structural condition of the vehicle from a location in the vehicle; and
a data acquisition unit 26 for storing the generated sensor signals at a first sampling rate.
15. The vehicle of Claim 14, wherein the data acquisition unit 26 determines whether the generated sensor signals are to be stored at the first sampling rate, and stores the generated sensor signals at a second sampling rate that is different than the first sampling rate when it is determined that the stored sensor signals are not to be stored at the first sampling rate.
16. The vehicle of Claim 14, wherein the one or more sensors 22 include at least one of a corrosion, humidity, pH, chloride ion, metal ion, temperature, acceleration, stress, strain, pressure, load, or force sensor.
17. The vehicle of Claim 14, wherein the data acquisition unit 26 performs preprocessing of the generated signals based on at least one of a diagnostic or prognostic algorithm.
18. A system for generating a maintenance plan for a vehicle, the system comprising:
- one or more sensors 22 for generating signals relating to a structural condition of the vehicle from a location in the vehicle;
a data acquisition unit 26 for storing the generated sensor signals at a first sampling rate; and
a structural condition management system 30 for receiving the stored sensor signals from the data acquisition unit, processing the received sensor signals based on one or more associated predefined condition assessment algorithms, and generating a maintenance plan based on the processed sensor signals, wherein the structural condition management system is external to the vehicle.
19. The system of Claim 18, wherein the data acquisition unit 26 determines whether the generated sensor signals are to be stored at the first sampling rate, and stores the generated sensor signals at a second sampling rate that is different than the first sampling rate when it is determined that the stored sensor signals are not to be stored at the first sampling rate.
20. The system of Claim 18, wherein the one or more sensors 22 include at least one of a corrosion, humidity, pH, chloride ion, metal ion, temperature, acceleration, stress, strain, pressure, load, or force sensor.
21. The system of Claim 18, wherein the data acquisition unit 26 performs preprocessing of the generated signals based on at least one of a diagnostic or prognostic algorithm.
22. The system of Claim 18, wherein one or more of the sensors 22 are fiber optic sensors.




Fig. 1.







Fig. 2.

*Fig. 3.*

*Fig. 4.*



(19)

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 353 252 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
26.11.2003 Bulletin 2003/48

(51) Int Cl.7: G05B 23/02, G01H 1/00

(43) Date of publication A2:
15.10.2003 Bulletin 2003/42

(21) Application number: 03075855.1

(22) Date of filing: 24.03.2003

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT RO SE SI SK TR
Designated Extension States:
AL LT LV MK

- Ikegami, Roy
Seattle, WA 98118 (US)
- Haugse, Eric D.
Normandy Park, WA 98166 (US)

(30) Priority: 04.04.2002 US 116653

(71) Applicant: THE BOEING COMPANY
Seattle, Washington 98124-2207 (US)

(74) Representative:
Land, Addick Adrianus Gosling et al
Arnold & Siedsma
Sweelinckplein 1
2517 GK Den Haag (NL)

(72) Inventors:
• Trego, Angela
Richland, WA 99352 (US)

(54) Vehicle condition monitoring system

(57) The present invention is a system and method for monitoring conditions of a vehicle and generating a maintenance plan according to the monitored conditions. The system includes one or more sensors 22 and a data acquisition unit 26 located within the vehicle 21. The one or more sensors 22 generate signals of a condition from various locations within the vehicle 21. The data acquisition unit 26 stores the generated sensor sig-

nals at a first sampling rate. The system also includes a structural condition management system 30 that receives the stored sensor signals from the data acquisition unit. The structural condition management system 30 is external to the vehicle 21. The structural condition management system 30 processes the transmitted sensor signals based on one or more associated predefined condition assessment algorithms and generates a maintenance plan based on the processed sensor signals.




Fig. 1.



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 03 07 5855

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 210 704 A (HUSSEINY ABD O A) 11 May 1993 (1993-05-11)	1,3,4,7, 8,12,17, 18 20	G05B23/02 G01H1/00
Y	* column 13, line 47 - column 17, line 42 *		
X	US 5 306 414 A (GLASS ROBERT S ET AL) 26 April 1994 (1994-04-26)	1,6,7, 12,14,16 20	
Y	* column 5, line 7 - column 6, line 39 * * column 8, line 35 - column 9, line 34 *		
X	US 5 195 046 A (GERARDI JOSEPH J ET AL) 16 March 1993 (1993-03-16)	1,7,14	
X	US 6 192 759 B1 (SCHOESS JEFFREY N) 27 February 2001 (2001-02-27)	1,7,14	
A	US 5 852 793 A (BOARD DAVID B ET AL) 22 December 1998 (1998-12-22)		
	* column 8, line 29 - column 9, line 41 *		
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			G05B G01H G05D G01M G01N
Place of search THE HAGUE		Date of completion of the search 23 September 2003	Examiner Kelperis, K
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 03 82 (POC01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 07 5855

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

23-09-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5210704	A	11-05-1993	NONE	
US 5306414	A	26-04-1994	US 5437773 A	01-08-1995
US 5195046	A	16-03-1993	US 5206806 A	27-04-1993
			US 5191791 A	09-03-1993
			US 5398547 A	21-03-1995
			WO 9008064 A1	26-07-1990
			US 5551288 A	03-09-1996
US 6192759	B1	27-02-2001	US 6076405 A	20-06-2000
			US 6014896 A	18-01-2000
			CA 2198737 A1	07-03-1996
			DE 69525629 D1	04-04-2002
			DE 69525629 T2	29-08-2002
			DE 69531315 D1	21-08-2003
			EP 1143242 A2	10-10-2001
			EP 0778942 A1	18-06-1997
			EP 0997714 A2	03-05-2000
			JP 10507259 T	14-07-1998
			WO 9607095 A1	07-03-1996
US 5852793	A	22-12-1998	EP 0961918 A1	08-12-1999
			WO 9836251 A1	20-08-1998

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82